

# A DYNAMIC PROBLEM WITH ADHESION AND DAMAGE IN ELECTRO-VISCOELASTICITY WITH LONG-TERM MEMORY

**SELMANI MOHAMED**

Department of Mathematics  
University of Setif, 19000 Setif Algeria  
EMail: [s\\_elmanih@yahoo.fr](mailto:s_elmanih@yahoo.fr)

*Received:* 24 October, 2007

*Accepted:* 24 February, 2009

*Communicated by:* **S.S. Dragomir**

*2000 AMS Sub. Class.:* 74M15, 74F99, 74H20, 74H25

*Key words:* Dynamic process, electro-viscoelastic material with long-term memory, frictionless contact, normal compliance, adhesion, damage, existence and uniqueness, monotone operator, fixed point, weak solution.

*Abstract:* We consider a dynamic frictionless contact problem for an electro-viscoelastic body with long-term memory and damage. The contact is modelled with normal compliance. The adhesion of the contact surfaces is taken into account and modelled by a surface variable, the bonding field. We derive variational formulation for the model which is formulated as a system involving the displacement field, the electric potential field, the damage field and the adhesion field. We prove the existence of a unique weak solution to the problem. The proof is based on arguments of evolution equations with monotone operators, parabolic inequalities, differential equations and fixed point.





Dynamic problem with adhesion and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

[Title Page](#)

[Contents](#)



Page 1 of 39

[Go Back](#)

[Full Screen](#)

[Close](#)

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756

# Contents

1	Introduction	3
2	Notation and Preliminaries	5
3	Mechanical and Variational Formulations	8
4	An Existence and Uniqueness Result	21



---

Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

---

Title Page

Contents



Page 2 of 39

Go Back

Full Screen


Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756

## 1. Introduction

The piezoelectric effect is the apparition of electric charges on surfaces of particular crystals after deformation. Its reverse effect consists of the generation of stress and strain in crystals under the action of the electric field on the boundary. Materials undergoing piezoelectric materials effects are called piezoelectric materials, and their study requires techniques and results from electromagnetic theory and continuum mechanics. Piezoelectric materials are used extensively as switches and, actually, in many engineering systems in radioelectronics, electroacoustics and measuring equipment. However, there are very few mathematical results concerning contact problems involving piezoelectric materials and therefore there is a need to extend the results on models for contact with deformable bodies which include coupling between mechanical and electrical properties. General models for elastic materials with piezoelectric effects can be found in [12, 13, 14, 22, 23] and more recently in [1, 21]. The adhesive contact between deformable bodies, when a glue is added to prevent relative motion of the surfaces, has also recently received increased attention in the mathematical literature. Analysis of models for adhesive contact can be found in [3, 4, 6, 7, 16, 17, 18] and recently in the monographs [19, 20]. The novelty in all these papers is the introduction of a surface internal variable, the bonding field, denoted in this paper by  $\alpha$ , which describes the pointwise fractional density of adhesion of active bonds on the contact surface, and is sometimes referred to as the intensity of adhesion. Following [6, 7], the bonding field satisfies the restriction  $0 \leq \alpha \leq 1$ . When  $\alpha = 1$  at a point of the contact surface, the adhesion is complete and all the bonds are active, when  $\alpha = 0$  all the bonds are inactive, severed, and there is no adhesion, when  $0 < \alpha < 1$  the adhesion is partial and only a fraction  $\alpha$  of the bonds is active. The importance of the paper lies in the coupling of the electric effect and the mechanical damage of the material. We study a dynamic problem of frictionless adhesive contact. We model the material with an electro-viscoelastic



Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

Title Page

Contents



Page 3 of 39

Go Back

Full Screen


Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756

constitutive law with long-term memory and damage. The contact is modelled with normal compliance. We derive a variational formulation and prove the existence and uniqueness of the weak solution.

The paper is structured as follows. In Section 2 we present notation and some preliminaries. The model is described in Section 3 where the variational formulation is given. In Section 4, we present our main result stated in Theorem 4.1 and its proof which is based on arguments of evolution equations with monotone operators, parabolic inequalities, differential equations and fixed points.



---

Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

---

Title Page

Contents



Page 4 of 39

Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756

## 2. Notation and Preliminaries

In this short section, we present the notation we shall use and some preliminary material. For more details, we refer the reader to [2, 5, 15]. We denote by  $S^d$  the space of second order symmetric tensors on  $\mathbb{R}^d$  ( $d = 2, 3$ ), while " $\cdot$ " and " $|\cdot|$ " represent the inner product and the Euclidean norm on  $S^d$  and  $\mathbb{R}^d$ , respectively. Let  $\Omega \subset \mathbb{R}^d$  be a bounded domain with a regular boundary  $\Gamma$  and let  $\nu$  denote the unit outer normal on  $\Gamma$ . We shall use the notation


$$\begin{aligned} H &= L^2(\Omega)^d = \{ \mathbf{u} = (u_i) / u_i \in L^2(\Omega) \}, \\ H^1(\Omega)^d &= \{ \mathbf{u} = (u_i) / u_i \in H^1(\Omega) \}, \\ \mathcal{H} &= \{ \sigma = (\sigma_{ij}) / \sigma_{ij} = \sigma_{ji} \in L^2(\Omega) \}, \\ \mathcal{H}_1 &= \{ \sigma \in \mathcal{H} / \text{Div } \sigma \in H \}, \end{aligned}$$

where  $\varepsilon : H^1(\Omega)^d \rightarrow \mathcal{H}$  and  $\text{Div} : \mathcal{H}_1 \rightarrow H$  are the deformation and divergence operators, respectively, defined by

$$\varepsilon(\mathbf{u}) = (\varepsilon_{ij}(\mathbf{u})), \quad \varepsilon_{ij}(\mathbf{u}) = \frac{1}{2}(u_{i,j} + u_{j,i}), \quad \text{Div } \sigma = (\sigma_{i,j,j}).$$

Here and below, the indices  $i$  and  $j$  run between 1 to  $d$ , the summation convention over repeated indices is used and the index that follows a comma indicates a partial derivative with respect to the corresponding component of the independent variable. The spaces  $H$ ,  $H^1(\Omega)^d$ ,  $\mathcal{H}$  and  $\mathcal{H}_1$  are real Hilbert spaces endowed with the canonical inner products given by

$$\begin{aligned} (\mathbf{u}, \mathbf{v})_H &= \int_{\Omega} \mathbf{u} \cdot \mathbf{v} \, dx \quad \forall \mathbf{u}, \mathbf{v} \in H, \\ (\mathbf{u}, \mathbf{v})_{H^1(\Omega)^d} &= \int_{\Omega} \mathbf{u} \cdot \mathbf{v} \, dx + \int_{\Omega} \nabla \mathbf{u} \cdot \nabla \mathbf{v} \, dx \quad \forall \mathbf{u}, \mathbf{v} \in H^1(\Omega)^d, \end{aligned}$$




Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

Title Page

Contents



Page 5 of 39

Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756

where

$$\begin{aligned}\nabla \mathbf{v} &= (v_{i,j}) \quad \forall \mathbf{v} \in H^1(\Omega)^d, \\ (\sigma, \tau)_{\mathcal{H}} &= \int_{\Omega} \sigma \cdot \tau \, dx \quad \forall \sigma, \tau \in \mathcal{H}, \\ (\sigma, \tau)_{\mathcal{H}_1} &= (\sigma, \tau)_{\mathcal{H}} + (\text{Div } \sigma, \text{Div } \tau)_H \quad \forall \sigma, \tau \in \mathcal{H}_1.\end{aligned}$$

The associated norms on the spaces  $H$ ,  $H^1(\Omega)^d$ ,  $\mathcal{H}$  and  $\mathcal{H}_1$  are denoted by  $|\cdot|_H$ ,  $|\cdot|_{H^1(\Omega)^d}$ ,  $|\cdot|_{\mathcal{H}}$  and  $|\cdot|_{\mathcal{H}_1}$  respectively. Let  $H_{\Gamma} = H^{\frac{1}{2}}(\Gamma)^d$  and let  $\gamma : H^1(\Omega)^d \rightarrow H_{\Gamma}$  be the trace map. For every element  $\mathbf{v} \in H^1(\Omega)^d$ , we also use the notation  $\mathbf{v}$  to denote the trace  $\gamma \mathbf{v}$  of  $\mathbf{v}$  on  $\Gamma$  and we denote by  $v_{\nu}$  and  $\mathbf{v}_{\tau}$  the normal and the tangential components of  $\mathbf{v}$  on the boundary  $\Gamma$  given by

$$(2.1) \quad v_{\nu} = \mathbf{v} \cdot \nu, \quad \mathbf{v}_{\tau} = \mathbf{v} - v_{\nu} \nu.$$

Similarly, for a regular (say  $C^1$ ) tensor field  $\sigma : \Omega \rightarrow S^d$  we define its normal and tangential components by


$$(2.2) \quad \sigma_{\nu} = (\sigma \nu) \cdot \nu, \quad \sigma_{\tau} = \sigma \nu - \sigma_{\nu} \nu,$$

and we recall that the following Green's formula holds:

$$(2.3) \quad (\sigma, \varepsilon(\mathbf{v}))_{\mathcal{H}} + (\text{Div } \sigma, \mathbf{v})_H = \int_{\Gamma} \sigma \nu \cdot \mathbf{v} \, da \quad \forall \mathbf{v} \in H^1(\Omega)^d.$$

$$(2.4) \quad (\mathbf{D}, \nabla \phi)_H + (\text{div } \mathbf{D}, \phi)_{L^2(\Omega)} = \int_{\Gamma} \mathbf{D} \cdot \nu \phi \, da \quad \forall \phi \in H^1(\Omega).$$

Finally, for any real Hilbert space  $X$ , we use the classical notation for the spaces  $L^p(0, T; X)$  and  $W^{k,p}(0, T; X)$ , where  $1 \leq p \leq +\infty$  and  $k \geq 1$ . We denote by



Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

Title Page

Contents



Page 6 of 39


Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756



$C(0, T; X)$  and  $C^1(0, T; X)$  the space of continuous and continuously differentiable functions from  $[0, T]$  to  $X$ , respectively, with the norms

$$\|f\|_{C(0,T;X)} = \max_{t \in [0,T]} \|f(t)\|_X,$$
$$\|f\|_{C^1(0,T;X)} = \max_{t \in [0,T]} \|f(t)\|_X + \max_{t \in [0,T]} \|\dot{f}(t)\|_X,$$

respectively. Moreover, we use the dot above to indicate the derivative with respect to the time variable and, for a real number  $r$ , we use  $r_+$  to represent its positive part, that is  $r_+ = \max\{0, r\}$ . For the convenience of the reader, we recall the following version of the classical theorem of Cauchy-Lipschitz (see, e.g., [20, p. 48]).

**Theorem 2.1.** *Assume that  $(X, \|\cdot\|_X)$  is a real Banach space and  $T > 0$ . Let  $F(t, \cdot) : X \rightarrow X$  be an operator defined a.e. on  $(0, T)$  satisfying the following conditions:*

1. *There exists a constant  $L_F > 0$  such that*

$$\|F(t, x) - F(t, y)\|_X \leq L_F \|x - y\|_X \quad \forall x, y \in X, \text{ a.e. } t \in (0, T).$$

2. *There exists  $p \geq 1$  such that  $t \mapsto F(t, x) \in L^p(0, T; X) \quad \forall x \in X$ .*

*Then for any  $x_0 \in X$ , there exists a unique function  $x \in W^{1,p}(0, T; X)$  such that*

$$\begin{aligned} \dot{x}(t) &= F(t, x(t)) & \text{a.e. } t \in (0, T), \\ x(0) &= x_0. \end{aligned}$$

Theorem 2.1 will be used in Section 4 to prove the unique solvability of the intermediate problem involving the bonding field. Moreover, if  $X_1$  and  $X_2$  are real Hilbert spaces then  $X_1 \times X_2$  denotes the product Hilbert space endowed with the canonical inner product  $(\cdot, \cdot)_{X_1 \times X_2}$ .

Dynamic problem with adhesion and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

Title Page

Contents



Page 7 of 39

Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756

© 2007 Victoria University. All rights reserved.


### 3. Mechanical and Variational Formulations

We describe the model for the process and present its variational formulation. The physical setting is the following. An electro-viscoelastic body occupies a bounded domain  $\Omega \subset \mathbb{R}^d$  ( $d = 2, 3$ ) with outer Lipschitz surface  $\Gamma$ . The body is submitted to the action of body forces of density  $\mathbf{f}_0$  and volume electric charges of density  $q_0$ . It is also submitted to mechanical and electric constraints on the boundary. We consider partitioning  $\Gamma$  into three disjoint measurable parts  $\Gamma_1, \Gamma_2$  and  $\Gamma_3$ , on one hand, and into two measurable parts  $\Gamma_a$  and  $\Gamma_b$ , on the other hand, such that  $meas(\Gamma_1) > 0$ ,  $meas(\Gamma_a) > 0$  and  $\Gamma_3 \subset \Gamma_b$ . Let  $T > 0$  and let  $[0, T]$  be the time interval of interest. The body is clamped on  $\Gamma_1 \times (0, T)$ , so the displacement field vanishes there. A surface traction of density  $\mathbf{f}_2$  acts on  $\Gamma_2 \times (0, T)$  and a body force of density  $\mathbf{f}_0$  acts in  $\Omega \times (0, T)$ . We also assume that the electrical potential vanishes on  $\Gamma_a \times (0, T)$  and a surface electric charge of density  $q_2$  is prescribed on  $\Gamma_b \times (0, T)$ . The body is in adhesive contact with an obstacle, or foundation, over the contact surface  $\Gamma_3$ . Moreover, the process is dynamic, and thus the inertial terms are included in the equation of motion. We denote by  $\mathbf{u}$  the displacement field, by  $\sigma$  the stress tensor field and by  $\varepsilon(\mathbf{u})$  the linearized strain tensor. We use an electro-viscoelastic constitutive law with long-term memory given by

$$\sigma = \mathcal{A}\varepsilon(\dot{\mathbf{u}}) + \mathcal{G}(\varepsilon(\mathbf{u}), \beta) + \int_0^t M(t-s)\varepsilon(\mathbf{u}(s)) ds - \mathcal{E}^*E(\varphi),$$

$$\mathbf{D} = \mathcal{E}\varepsilon(\mathbf{u}) + BE(\varphi),$$

where  $\mathcal{A}$  is a given nonlinear function,  $M$  is the relaxation tensor, and  $\mathcal{G}$  represents the elasticity operator where  $\beta$  is an internal variable describing the damage of the material caused by elastic deformations.  $E(\varphi) = -\nabla\varphi$  is the electric field,  $\mathcal{E} = (e_{ijk})$  represents the third order piezoelectric tensor,  $\mathcal{E}^*$  is its transposition and  $B$



Dynamic problem with adhesion and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

Title Page

Contents



Page 8 of 39

Go Back


Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756





Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 9 of 39

Go Back

Full Screen

Close

denotes the electric permittivity tensor. The inclusion used for the evolution of the damage field is

$$\dot{\beta} - k \Delta \beta + \partial \varphi_K(\beta) \ni S(\varepsilon(\mathbf{u}), \beta),$$

where  $K$  denotes the set of admissible damage functions defined by

$$K = \{\xi \in H^1(\Omega) / 0 \leq \xi \leq 1 \quad \text{a.e. in } \Omega\},$$


$k$  is a positive coefficient,  $\partial \varphi_K$  denotes the subdifferential of the indicator function  $\varphi_K$  and  $S$  is a given constitutive function which describes the sources of the damage in the system. When  $\beta = 1$  the material is undamaged, when  $\beta = 0$  the material is completely damaged, and for  $0 < \beta < 1$  there is partial damage. General models of mechanical damage, which were derived from thermodynamical considerations and the principle of virtual work, can be found in [8] and [9] and references therein. The models describe the evolution of the material damage which results from the excess tension or compression in the body as a result of applied forces and tractions. Mathematical analysis of one-dimensional damage models can be found in [10].

To simplify the notation, we do not indicate explicitly the dependence of various functions on the variables  $\mathbf{x} \in \Omega \cup \Gamma$  and  $t \in [0, T]$ . Then, the classical formulation of the mechanical problem of electro-viscoelastic material, frictionless, adhesive contact may be stated as follows.

**Problem P.** Find a displacement field  $\mathbf{u} : \Omega \times [0, T] \rightarrow \mathbb{R}^d$ , a stress field  $\sigma : \Omega \times [0, T] \rightarrow S^d$ , an electric potential field  $\varphi : \Omega \times [0, T] \rightarrow \mathbb{R}$ , an electric displacement field  $\mathbf{D} : \Omega \times [0, T] \rightarrow \mathbb{R}^d$ , a damage field  $\beta : \Omega \times [0, T] \rightarrow \mathbb{R}$  and a bonding field  $\alpha : \Gamma_3 \times [0, T] \rightarrow \mathbb{R}$  such that

$$(3.1) \quad \sigma = \mathcal{A}\varepsilon(\dot{\mathbf{u}}) + \mathcal{G}(\varepsilon(\mathbf{u}), \beta) + \int_0^t M(t-s)\varepsilon(\mathbf{u}(s)) ds + \mathcal{E}^* \nabla \varphi \quad \text{in } \Omega \times (0, T),$$

$$(3.2) \quad \mathbf{D} = \mathcal{E}\varepsilon(\mathbf{u}) - B\nabla \varphi \quad \text{in } \Omega \times (0, T),$$



Title Page

Contents



Page 10 of 39

Go Back

Full Screen

Close

$$(3.3) \quad \dot{\beta} - k \Delta \beta + \partial \varphi_K(\beta) \ni S(\varepsilon(\mathbf{u}), \beta) \quad \text{in } \Omega \times (0, T),$$

$$(3.4) \quad \rho \ddot{\mathbf{u}} = \text{Div } \sigma + \mathbf{f}_0 \quad \text{in } \Omega \times (0, T),$$

$$(3.5) \quad \text{div } \mathbf{D} = q_0 \quad \text{in } \Omega \times (0, T),$$

$$(3.6) \quad \mathbf{u} = 0 \quad \text{on } \Gamma_1 \times (0, T),$$


$$(3.7) \quad \sigma \nu = \mathbf{f}_2 \quad \text{on } \Gamma_2 \times (0, T),$$

$$(3.8) \quad -\sigma_\nu = p_\nu(u_\nu) - \gamma_\nu \alpha^2 R_\nu(u_\nu) \quad \text{on } \Gamma_3 \times (0, T),$$

$$(3.9) \quad -\sigma_\tau = p_\tau(\alpha) \mathbf{R}_\tau(\mathbf{u}_\tau) \quad \text{on } \Gamma_3 \times (0, T),$$

$$(3.10) \quad \dot{\alpha} = -(\alpha(\gamma_\nu(R_\nu(u_\nu))^2 + \gamma_\tau |\mathbf{R}_\tau(\mathbf{u}_\tau)|^2) - \varepsilon_a)_+ \quad \text{on } \Gamma_3 \times (0, T),$$

$$(3.11) \quad \frac{\partial \beta}{\partial \nu} = 0 \quad \text{on } \Gamma_3 \times (0, T),$$



$$(3.12) \quad \varphi = 0 \quad \text{on} \quad \Gamma_a \times (0, T),$$

$$(3.13) \quad \mathbf{D} \cdot \nu = q_2 \quad \text{on} \quad \Gamma_b \times (0, T),$$

$$(3.14) \quad \mathbf{u}(0) = \mathbf{u}_0, \dot{\mathbf{u}}(0) = \mathbf{v}_0, \beta(0) = \beta_0 \quad \text{in} \quad \Omega,$$

$$(3.15) \quad \alpha(0) = \alpha_0 \quad \text{on} \quad \Gamma_3.$$

First, (3.1) and (3.2) represent the electro-viscoelastic constitutive law with long term-memory and damage, the evolution of the damage field is governed by the inclusion of parabolic type given by the relation (3.3), where  $S$  is the mechanical source of the damage, and  $\partial\varphi_K$  is the subdifferential of the indicator function of the admissible damage functions set  $K$ . Equations (3.4) and (3.5) represent the equation of motion for the stress field and the equilibrium equation for the electric-displacement field while (3.6) and (3.7) are the displacement and traction boundary condition, respectively. Condition (3.8) represents the normal compliance condition with adhesion where  $\gamma_\nu$  is a given adhesion coefficient and  $p_\nu$  is a given positive function which will be described below. In this condition the interpenetrability between the body and the foundation is allowed, that is  $u_\nu$  can be positive on  $\Gamma_3$ . The contribution of the adhesive to the normal traction is represented by the term  $\gamma_\nu \alpha^2 R_\nu(u_\nu)$ , the adhesive traction is tensile and is proportional, with proportionality coefficient  $\gamma_\nu$ , to the square of the intensity of adhesion and to the normal displacement, but only as long as it does not exceed the bond length  $L$ . The maximal tensile

Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 11 of 39

Go Back

Full Screen

Close

traction is  $\gamma_\nu L$ .  $R_\nu$  is the truncation operator defined by


$$R_\nu(s) = \begin{cases} L & \text{if } s < -L, \\ -s & \text{if } -L \leq s \leq 0, \\ 0 & \text{if } s > 0. \end{cases}$$

Here  $L > 0$  is the characteristic length of the bond, beyond which it does not offer any additional traction. The introduction of the operator  $R_\nu$ , together with the operator  $\mathbf{R}_\tau$  defined below, is motivated by mathematical arguments but it is not restrictive from the physical point of view, since no restriction on the size of the parameter  $L$  is made in what follows. Condition (3.9) represents the adhesive contact condition on the tangential plane, in which  $p_\tau$  is a given function and  $\mathbf{R}_\tau$  is the truncation operator given by

$$\mathbf{R}_\tau(\mathbf{v}) = \begin{cases} \mathbf{v} & \text{if } |\mathbf{v}| \leq L, \\ L \frac{\mathbf{v}}{|\mathbf{v}|} & \text{if } |\mathbf{v}| > L. \end{cases}$$

This condition shows that the shear on the contact surface depends on the bonding field and on the tangential displacement, but only as long as it does not exceed the bond length  $L$ . The frictional tangential traction is assumed to be much smaller than the adhesive one and, therefore, omitted.

Next, the equation (3.10) is an ordinary differential equation which describes the evolution of the bonding field and it has already been used in [3], see also [19, 20] for more details. Here, besides  $\gamma_\nu$ , two new adhesion coefficients are involved,  $\gamma_\tau$  and  $\varepsilon_a$ . Notice that in this model, once debonding occurs bonding cannot be re-established since, from (3.10),  $\dot{\alpha} \leq 0$ . The relation (3.11) represents a homogeneous Neumann boundary condition where  $\frac{\partial \beta}{\partial \nu}$  represents the normal derivative of  $\beta$ . (3.12) and (3.13) represent the electric boundary conditions. (3.14) represents the initial



Title Page

Contents

◀◀ ▶▶


◀ ▶

Page 12 of 39

Go Back

Full Screen

Close



displacement field, the initial velocity and the initial damage field. Finally (3.15) represents the initial condition in which  $\alpha_0$  is the given initial bonding field. To obtain the variational formulation of the problems (3.1) – (3.15), we introduce for the bonding field the set

$$Z = \{ \theta \in L^\infty(0, T; L^2(\Gamma_3)) / 0 \leq \theta(t) \leq 1 \forall t \in [0, T], \text{ a.e. on } \Gamma_3 \},$$

and for the displacement field we need the closed subspace of  $H^1(\Omega)^d$  defined by

$$V = \{ \mathbf{v} \in H^1(\Omega)^d / \mathbf{v} = 0 \text{ on } \Gamma_1 \}.$$

Since  $meas(\Gamma_1) > 0$ , Korn's inequality holds and there exists a constant  $C_k > 0$ , that depends only on  $\Omega$  and  $\Gamma_1$ , such that

$$|\varepsilon(\mathbf{v})|_{\mathcal{H}} \geq C_k |\mathbf{v}|_{H^1(\Omega)^d} \quad \forall \mathbf{v} \in V.$$

A proof of Korn's inequality may be found in [15, p. 79]. On the space  $V$  we consider the inner product and the associated norm given by

$$(3.16) \quad (\mathbf{u}, \mathbf{v})_V = (\varepsilon(\mathbf{u}), \varepsilon(\mathbf{v}))_{\mathcal{H}}, \quad |\mathbf{v}|_V = |\varepsilon(\mathbf{v})|_{\mathcal{H}} \quad \forall \mathbf{u}, \mathbf{v} \in V.$$

It follows that  $|\cdot|_{H^1(\Omega)^d}$  and  $|\cdot|_V$  are equivalent norms on  $V$  and therefore  $(V, |\cdot|_V)$  is a real Hilbert space. Moreover, by the Sobolev trace Theorem and (3.16), there exists a constant  $C_0 > 0$ , depending only on  $\Omega$ ,  $\Gamma_1$  and  $\Gamma_3$  such that

$$(3.17) \quad |\mathbf{v}|_{L^2(\Gamma_3)^d} \leq C_0 |\mathbf{v}|_V \quad \forall \mathbf{v} \in V.$$

We also introduce the spaces

$$W = \{ \phi \in H^1(\Omega) / \phi = 0 \text{ on } \Gamma_a \},$$

$$\mathcal{W} = \{ \mathbf{D} = (D_i) / D_i \in L^2(\Omega), \text{ div } \mathbf{D} \in L^2(\Omega) \},$$

where  $\operatorname{div} \mathbf{D} = (D_{i,i})$ . The spaces  $W$  and  $\mathcal{W}$  are real Hilbert spaces with the inner products given by

$$(\varphi, \phi)_W = \int_{\Omega} \nabla \varphi \cdot \nabla \phi \, dx,$$


$$(\mathbf{D}, \mathbf{E})_{\mathcal{W}} = \int_{\Omega} \mathbf{D} \cdot \mathbf{E} \, dx + \int_{\Omega} \operatorname{div} \mathbf{D} \cdot \operatorname{div} \mathbf{E} \, dx.$$

The associated norms will be denoted by  $|\cdot|_W$  and  $|\cdot|_{\mathcal{W}}$ , respectively. Notice also that, since  $\operatorname{meas}(\Gamma_a) > 0$ , the following Friedrichs-Poincaré inequality holds:

$$(3.18) \quad |\nabla \phi|_H \geq C_F |\phi|_{H^1(\Omega)} \quad \forall \phi \in W,$$

where  $C_F > 0$  is a constant which depends only on  $\Omega$  and  $\Gamma_a$ . In the study of the mechanical problems (3.1) – (3.15), we assume that the viscosity function  $\mathcal{A} : \Omega \times S^d \rightarrow S^d$  satisfies

$$(3.19) \quad \left\{ \begin{array}{l} (a) \text{ There exists constants } C_1^{\mathcal{A}}, C_2^{\mathcal{A}} > 0 \text{ such that} \\ \quad |\mathcal{A}(\mathbf{x}, \varepsilon)| \leq C_1^{\mathcal{A}} |\varepsilon| + C_2^{\mathcal{A}} \quad \forall \varepsilon \in S^d, \text{ a.e. } \mathbf{x} \in \Omega. \\ (b) \text{ There exists a constant } m_{\mathcal{A}} > 0 \text{ Such that} \\ \quad (\mathcal{A}(\mathbf{x}, \varepsilon_1) - \mathcal{A}(\mathbf{x}, \varepsilon_2)) \cdot (\varepsilon_1 - \varepsilon_2) \geq m_{\mathcal{A}} |\varepsilon_1 - \varepsilon_2|^2 \\ \quad \forall \varepsilon_1, \varepsilon_2 \in S^d, \text{ a.e. } \mathbf{x} \in \Omega. \\ (c) \text{ The mapping } \mathbf{x} \rightarrow \mathcal{A}(\mathbf{x}, \varepsilon) \text{ is Lebesgue measurable on} \\ \quad \Omega \text{ for any } \varepsilon \in S^d. \\ (d) \text{ The mapping } \varepsilon \rightarrow \mathcal{A}(\mathbf{x}, \varepsilon) \text{ is continuous on } S^d, \text{ a.e. } \mathbf{x} \in \Omega. \end{array} \right.$$



Title Page

Contents




Page 14 of 39

Go Back

Full Screen

Close



Title Page

Contents



Page 15 of 39

Go Back

Full Screen

Close

The elasticity Operator  $\mathcal{G} : \Omega \times S^d \times \mathbb{R} \rightarrow S^d$  satisfies


$$(3.20) \quad \left\{ \begin{array}{l} (a) \quad \text{There exists a constant } L_{\mathcal{G}} > 0 \text{ Such that} \\ \quad |\mathcal{G}(\mathbf{x}, \varepsilon_1, \alpha_1) - \mathcal{G}(\mathbf{x}, \varepsilon_2, \alpha_2)| \leq L_{\mathcal{G}}(|\varepsilon_1 - \varepsilon_2| + |\alpha_1 - \alpha_2|) \\ \quad \forall \varepsilon_1, \varepsilon_2 \in S^d, \forall \alpha_1, \alpha_2 \in \mathbb{R} \text{ a.e. } \mathbf{x} \in \Omega. \\ (b) \quad \text{The mapping } \mathbf{x} \rightarrow \mathcal{G}(\mathbf{x}, \varepsilon, \alpha) \text{ is Lebesgue measurable on } \Omega \\ \quad \text{for any } \varepsilon \in S^d \text{ and } \alpha \in \mathbb{R}. \\ (c) \quad \text{The mapping } \mathbf{x} \rightarrow \mathcal{G}(\mathbf{x}, \mathbf{0}, 0) \text{ belongs to } \mathcal{H}. \end{array} \right.$$

The damage source function  $S : \Omega \times S^d \times \mathbb{R} \rightarrow \mathbb{R}$  satisfies

$$(3.21) \quad \left\{ \begin{array}{l} (a) \quad \text{There exists a constant } L_S > 0 \text{ such that} \\ \quad |S(\mathbf{x}, \varepsilon_1, \alpha_1) - S(\mathbf{x}, \varepsilon_2, \alpha_2)| \leq L_S(|\varepsilon_1 - \varepsilon_2| + |\alpha_1 - \alpha_2|) \\ \quad \forall \varepsilon_1, \varepsilon_2 \in S^d, \forall \alpha_1, \alpha_2 \in \mathbb{R} \text{ a.e. } \mathbf{x} \in \Omega. \\ (b) \quad \text{For any } \varepsilon \in S^d \text{ and } \alpha \in \mathbb{R}, \mathbf{x} \rightarrow S(\mathbf{x}, \varepsilon, \alpha) \text{ is} \\ \quad \text{Lebesgue measurable on } \Omega. \\ (c) \quad \text{The mapping } \mathbf{x} \rightarrow S(\mathbf{x}, \mathbf{0}, 0) \text{ belongs to } L^2(\Omega). \end{array} \right.$$

The electric permittivity operator  $B = (b_{ij}) : \Omega \times \mathbb{R}^d \rightarrow \mathbb{R}^d$  satisfies

$$(3.22) \quad \left\{ \begin{array}{l} (a) \quad B(\mathbf{x}, \mathbf{E}) = (b_{ij}(\mathbf{x})E_j) \quad \forall \mathbf{E} = (E_i) \in \mathbb{R}^d, \text{ a.e. } \mathbf{x} \in \Omega. \\ (b) \quad b_{ij} = b_{ji}, \quad b_{ij} \in L^\infty(\Omega), \quad 1 \leq i, j \leq d. \\ (c) \quad \text{There exists a constant } m_B > 0 \quad \text{such that} \\ \quad B\mathbf{E} \cdot \mathbf{E} \geq m_B |\mathbf{E}|^2 \quad \forall \mathbf{E} = (E_i) \in \mathbb{R}^d, \quad \text{a.e. in } \Omega. \end{array} \right.$$



The piezoelectric operator  $\mathcal{E} : \Omega \times S^d \rightarrow \mathbb{R}^d$  satisfies

$$(3.23) \quad \begin{cases} (a) & \mathcal{E}(\mathbf{x}, \tau) = (e_{ijk}(\mathbf{x})\tau_{jk}) \quad \forall \tau = (\tau_{ij}) \in S^d, \text{ a.e. } \mathbf{x} \in \Omega. \\ (b) & e_{ijk} = e_{ikj} \in L^\infty(\Omega), \quad 1 \leq i, j, k \leq d. \end{cases}$$

The normal compliance function  $p_\nu : \Gamma_3 \times \mathbb{R} \rightarrow \mathbb{R}_+$  satisfies

$$(3.24) \quad \begin{cases} (a) & \text{There exists a constant } L_\nu > 0 \text{ such that} \\ & |p_\nu(\mathbf{x}, r_1) - p_\nu(\mathbf{x}, r_2)| \leq L_\nu |r_1 - r_2| \quad \forall r_1, r_2 \in \mathbb{R}, \text{ a.e. } \mathbf{x} \in \Gamma_3. \\ (b) & \text{The mapping } \mathbf{x} \rightarrow p_\nu(\mathbf{x}, r) \text{ is measurable on } \Gamma_3, \text{ for any } r \in \mathbb{R}. \\ (c) & p_\nu(\mathbf{x}, r) = 0 \text{ for all } r \leq 0, \text{ a.e. } \mathbf{x} \in \Gamma_3. \end{cases}$$


The tangential contact function  $p_\tau : \Gamma_3 \times \mathbb{R} \rightarrow \mathbb{R}_+$  satisfies

$$(3.25) \quad \begin{cases} (a) & \text{There exists a constant } L_\tau > 0 \text{ such that} \\ & |p_\tau(\mathbf{x}, d_1) - p_\tau(\mathbf{x}, d_2)| \leq L_\tau |d_1 - d_2| \quad \forall d_1, d_2 \in \mathbb{R}, \\ & \text{a.e. } \mathbf{x} \in \Gamma_3. \\ (b) & \text{There exists } M_\tau > 0 \text{ such that } |p_\tau(\mathbf{x}, d)| \leq M_\tau \quad \forall d \in \mathbb{R}, \\ & \text{a.e. } \mathbf{x} \in \Gamma_3. \\ (c) & \text{The mapping } \mathbf{x} \rightarrow p_\tau(\mathbf{x}, d) \text{ is measurable on } \Gamma_3, \text{ for any } d \in \mathbb{R}. \\ (d) & \text{The mapping } \mathbf{x} \rightarrow p_\tau(\mathbf{x}, 0) \in L^2(\Gamma_3). \end{cases}$$

The relaxation tensor  $M$  satisfies

$$(3.26) \quad M \in C(0, T; \mathcal{H}).$$





We suppose that the mass density satisfies

$$(3.27) \quad \rho \in L^\infty(\Omega), \text{ there exists } \rho^* > 0 \text{ such that } \rho(\mathbf{x}) \geq \rho^* \text{ a.e. } \mathbf{x} \in \Omega.$$

We also suppose that the body forces and surface tractions have the regularity

$$(3.28) \quad \mathbf{f}_0 \in L^2(0, T; H), \quad \mathbf{f}_2 \in L^2(0, T; L^2(\Gamma_2)^d),$$

$$(3.29) \quad q_0 \in C(0, T; L^2(\Omega)), \quad q_2 \in C(0, T; L^2(\Gamma_b)).$$

$$(3.30) \quad q_2(t) = 0 \text{ on } \Gamma_3 \quad \forall t \in [0, T].$$

Note that we need to impose assumption (3.30) for physical reasons. Indeed the foundation is assumed to be insulator and therefore the electric charges (which are prescribed on  $\Gamma_b \supset \Gamma_3$ ) have to vanish on the potential contact surface. The adhesion coefficients satisfy

$$(3.31) \quad \gamma_\nu, \gamma_\tau \in L^\infty(\Gamma_3), \quad \varepsilon_a \in L^2(\Gamma_3), \quad \gamma_\nu, \gamma_\tau, \varepsilon_a \geq 0 \quad \text{a.e. on } \Gamma_3.$$

The initial displacement field satisfies


$$(3.32) \quad \mathbf{u}_0 \in V, \quad \mathbf{v}_0 \in H,$$

the initial bonding field satisfies

$$(3.33) \quad \alpha_0 \in L^2(\Gamma_3), \quad 0 \leq \alpha_0 \leq 1 \text{ a.e. on } \Gamma_3,$$

and the initial damage field satisfies

$$(3.34) \quad \beta_0 \in K.$$



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 18 of 39

Go Back

Full Screen

Close

We define the bilinear form  $a : H^1(\Omega) \times H^1(\Omega) \rightarrow \mathbb{R}$  by

$$(3.35) \quad a(\xi, \varphi) = k \int_{\Omega} \nabla \xi \cdot \nabla \varphi \, dx.$$

We will use a modified inner product on  $H = L^2(\Omega)^d$ , given by

$$((\mathbf{u}, \mathbf{v}))_H = (\rho \mathbf{u}, \mathbf{v})_H \quad \forall \mathbf{u}, \mathbf{v} \in H,$$

that is, it is weighted with  $\rho$ , and we let  $\|\cdot\|_H$  be the associated norm, i.e.,

$$\|\mathbf{v}\|_H = (\rho \mathbf{v}, \mathbf{v})_H^{\frac{1}{2}} \quad \forall \mathbf{v} \in H.$$

It follows from assumption (3.27) that  $\|\cdot\|_H$  and  $|\cdot|_H$  are equivalent norms on  $H$ , and the inclusion mapping of  $(V, |\cdot|_V)$  into  $(H, \|\cdot\|_H)$  is continuous and dense. We denote by  $V'$  the dual of  $V$ . Identifying  $H$  with its own dual, we can write the Gelfand triple

$$V \subset H \subset V'.$$

Using the notation  $(\cdot, \cdot)_{V' \times V}$  to represent the duality pairing between  $V'$  and  $V$ , we have


$$(\mathbf{u}, \mathbf{v})_{V' \times V} = ((\mathbf{u}, \mathbf{v}))_H \quad \forall \mathbf{u} \in H, \forall \mathbf{v} \in V.$$

Finally, we denote by  $|\cdot|_{V'}$  the norm on  $V'$ . Assumption (3.28) allows us, for a.e.  $t \in (0, T)$ , to define  $\mathbf{f}(t) \in V'$  by

$$(3.36) \quad (\mathbf{f}(t), \mathbf{v})_{V' \times V} = \int_{\Omega} \mathbf{f}_0(t) \cdot \mathbf{v} \, dx + \int_{\Gamma_2} \mathbf{f}_2(t) \cdot \mathbf{v} \, da \quad \forall \mathbf{v} \in V.$$

We denote by  $q : [0, T] \rightarrow W$  the function defined by

$$(3.37) \quad (q(t), \phi)_W = \int_{\Omega} q_0(t) \cdot \phi \, dx - \int_{\Gamma_b} q_2(t) \cdot \phi \, da \quad \forall \phi \in W, t \in [0, T].$$



Next, we denote by  $j : L^\infty(\Gamma_3) \times V \times V \rightarrow \mathbb{R}$  the adhesion functional defined by

$$(3.38) \quad j(\alpha, \mathbf{u}, \mathbf{v}) = \int_{\Gamma_3} p_\nu(u_\nu) v_\nu \, da + \int_{\Gamma_3} (-\gamma_\nu \alpha^2 R_\nu(u_\nu) v_\nu + p_\tau(\alpha) \mathbf{R}_\tau(\mathbf{u}_\tau) \cdot \mathbf{v}_\tau) \, da.$$

Keeping in mind (3.24) – (3.25), we observe that the integrals (3.38) are well defined and we note that conditions (3.28) – (3.29) imply


$$(3.39) \quad \mathbf{f} \in L^2(0, T; V'), \quad q \in C(0, T; W).$$

Using standard arguments we obtain the variational formulation of the mechanical problem (3.1) – (3.15).

**Problem PV.** Find a displacement field  $\mathbf{u} : [0, T] \rightarrow V$ , an electric potential field  $\varphi : [0, T] \rightarrow W$ , a damage field  $\beta : [0, T] \rightarrow H^1(\Omega)$  and a bonding field  $\alpha : [0, T] \rightarrow L^\infty(\Gamma_3)$  such that

$$(3.40) \quad (\ddot{\mathbf{u}}, \mathbf{v})_{V' \times V} + (\mathcal{A}\varepsilon(\dot{\mathbf{u}}(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} + (\mathcal{G}(\varepsilon(\mathbf{u}(t)), \beta(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} + \left( \int_0^t M(t-s) \varepsilon(\mathbf{u}(s)) ds, \varepsilon(\mathbf{v}) \right)_{\mathcal{H}} + (\mathcal{E}^* \nabla \varphi(t), \varepsilon(\mathbf{v}))_{\mathcal{H}} + j(\alpha(t), \mathbf{u}(t), \mathbf{v}) = (\mathbf{f}(t), \mathbf{v})_{V' \times V} \quad \forall \mathbf{v} \in V, t \in (0, T),$$

$$(3.41) \quad \beta(t) \in K \text{ for all } t \in [0, T], \quad \left( \dot{\beta}(t), \xi - \beta(t) \right)_{L^2(\Omega)} + a(\beta(t), \xi - \beta(t)) \geq (S(\varepsilon(\mathbf{u}(t)), \beta(t)), \xi - \beta(t))_{L^2(\Omega)} \quad \forall \xi \in K,$$



Title Page

Contents



Page 20 of 39

Go Back

Full Screen

Close

$$(3.42) \quad (B\nabla\varphi(t), \nabla\phi)_H - (\mathcal{E}\varepsilon(\mathbf{u}(t)), \nabla\phi)_H = (q(t), \phi)_W \quad \forall\phi \in W, t \in (0, T),$$

$$(3.43) \quad \dot{\alpha}(t) = -(\alpha(t) [\gamma_\nu (R_\nu(u_\nu(t)))^2 + \gamma_\tau |\mathbf{R}_\tau(\mathbf{u}_\tau(t))|^2] - \varepsilon_a)_+ \quad \text{a.e. } t \in (0, T),$$

$$(3.44) \quad \mathbf{u}(0) = \mathbf{u}_0, \quad \dot{\mathbf{u}}(0) = \mathbf{v}_0, \quad \beta(0) = \beta_0, \quad \alpha(0) = \alpha_0.$$

We notice that the variational problem  $PV$  is formulated in terms of a displacement field, an electrical potential field, a damage field and a bonding field. The existence of the unique solution of problem  $PV$  is stated and proved in the next section. To this end, we consider the following remark which is used in different places of the paper.

*Remark 1.* We note that, in the problem  $P$  and in the problem  $PV$  we do not need to impose explicitly the restriction  $0 \leq \alpha \leq 1$ . Indeed, equations (3.43) guarantee that  $\alpha(\mathbf{x}, t) \leq \alpha_0(\mathbf{x})$  and, therefore, assumption (3.33) shows that  $\alpha(\mathbf{x}, t) \leq 1$  for  $t \geq 0$ , a.e.  $\mathbf{x} \in \Gamma_3$ . On the other hand, if  $\alpha(\mathbf{x}, t_0) = 0$  at time  $t_0$ , then it follows from (3.43) that  $\dot{\alpha}(\mathbf{x}, t) = 0$  for all  $t \geq t_0$  and therefore,  $\alpha(\mathbf{x}, t) = 0$  for all  $t \geq t_0$ , a.e.  $\mathbf{x} \in \Gamma_3$ . We conclude that  $0 \leq \alpha(\mathbf{x}, t) \leq 1$  for all  $t \in [0, T]$ , a.e.  $\mathbf{x} \in \Gamma_3$ .

## 4. An Existence and Uniqueness Result

Now, we propose our existence and uniqueness result.

**Theorem 4.1.** *Assume that (3.19) – (3.34) hold. Then there exists a unique solution  $\{\mathbf{u}, \varphi, \beta, \alpha\}$  to problem PV. Moreover, the solution satisfies*

$$(4.1) \quad \mathbf{u} \in H^1(0, T; V) \cap C^1(0, T; H), \quad \ddot{\mathbf{u}} \in L^2(0, T; V'),$$

$$(4.2) \quad \varphi \in C(0, T; W),$$


$$(4.3) \quad \beta \in W^{1,2}(0, T; L^2(\Omega)) \cap L^2(0, T; H^1(\Omega)),$$

$$(4.4) \quad \alpha \in W^{1,\infty}(0, T; L^2(\Gamma_3)) \cap Z.$$

The functions  $\mathbf{u}, \varphi, \sigma, \mathbf{D}, \beta$  and  $\alpha$  which satisfy (3.1) – (3.2) and (3.40) – (3.44) are called weak solutions of the contact problem  $P$ . We conclude that, under the assumptions (3.19) – (3.34), the mechanical problem (3.1) – (3.15) has a unique weak solution satisfying (4.1) – (4.4). The regularity of the weak solution is given by (4.1) – (4.4) and, in term of stresses,

$$(4.5) \quad \sigma \in L^2(0, T; \mathcal{H}), \quad \text{Div } \sigma \in L^2(0, T; V'),$$

$$(4.6) \quad \mathbf{D} \in C(0, T; \mathcal{W}).$$



Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

Title Page

Contents



Page 21 of 39


Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756



Indeed, it follows from (3.40) and (3.42) that  $\rho \ddot{\mathbf{u}} = \text{Div } \sigma(t) + \mathbf{f}_0(t)$ ,  $\text{div } \mathbf{D} = q_0(t)$  for all  $t \in [0, T]$ . Therefore the regularity (4.1) and (4.2) of  $\mathbf{u}$  and  $\varphi$ , combined with (3.19) – (3.29) implies (4.5) and (4.6).

The proof of Theorem 4.1 is carried out in several steps that we prove in what follows. Everywhere in this section we suppose that the assumptions of Theorem 4.1 hold, and we assume that  $C$  is a generic positive constant which depends on  $\Omega, \Gamma_1, \Gamma_3, p_\nu, p_\tau, \gamma_\nu, \gamma_\tau$  and  $L$  and may change from place to place. Let  $\eta \in L^2(0, T; V')$  be given, in the first step we consider the following variational problem.

**Problem  $PV_\eta$ .** Find a displacement field  $\mathbf{u}_\eta : [0, T] \rightarrow V$  such that


$$(4.7) \quad (\ddot{\mathbf{u}}_\eta(t), \mathbf{v})_{V' \times V} + (\mathcal{A}\varepsilon(\dot{\mathbf{u}}_\eta(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} + (\eta(t), \mathbf{v})_{V' \times V} = (\mathbf{f}(t), \mathbf{v})_{V' \times V} \quad \forall \mathbf{v} \in V \text{ a.e. } t \in (0, T),$$

$$(4.8) \quad \mathbf{u}_\eta(0) = \mathbf{u}_0, \quad \eta(0) = \mathbf{v}_0.$$

To solve problem  $PV_\eta$ , we apply an abstract existence and uniqueness result which we recall now, for the convenience of the reader. Let  $V$  and  $H$  denote real Hilbert spaces such that  $V$  is dense in  $H$  and the inclusion map is continuous,  $H$  is identified with its dual and with a subspace of the dual  $V'$  of  $V$ , i.e.,  $V \subset H \subset V'$ , and we say that the inclusions above define a Gelfand triple. The notations  $|\cdot|_V, |\cdot|_{V'}$  and  $(\cdot, \cdot)_{V' \times V}$  represent the norms on  $V$  and on  $V'$  and the duality pairing between them, respectively. The following abstract result may be found in [20, p. 48].

**Theorem 4.2.** Let  $V, H$  be as above, and let  $A : V \rightarrow V'$  be a hemicontinuous and monotone operator which satisfies

$$(4.9) \quad (A\mathbf{v}, \mathbf{v})_{V' \times V} \geq \omega |\mathbf{v}|_V^2 + \lambda \quad \forall \mathbf{v} \in V,$$



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 23 of 39

Go Back

Full Screen

Close

$$(4.10) \quad |A\mathbf{v}|_{V'} \leq C(|\mathbf{v}|_V + 1) \quad \forall \mathbf{v} \in V,$$

for some constants  $\omega > 0$ ,  $C > 0$  and  $\lambda \in \mathbb{R}$ . Then, given  $\mathbf{u}_0 \in H$  and  $\mathbf{f} \in L^2(0, T; V')$ , there exists a unique function  $\mathbf{u}$  which satisfies

$$\begin{aligned} \mathbf{u} \in L^2(0, T; V') \cap C(0, T; H), \quad \dot{\mathbf{u}} \in L^2(0, T; V'), \\ \dot{\mathbf{u}}(t) + A\mathbf{u}(t) = \mathbf{f}(t) \quad \text{a.e. } t \in (0, T), \\ \mathbf{u}(0) = \mathbf{u}_0. \end{aligned}$$

We apply it to problem  $PV_\eta$ .

**Lemma 4.3.** *There exists a unique solution to problem  $PV_\eta$  and it has its regularity expressed in (4.1).*

*Proof.* We define the operator  $A : V \rightarrow V'$  by


$$(4.11) \quad (A\mathbf{u}, \mathbf{v})_{V' \times V} = (\mathcal{A}\varepsilon(\mathbf{u}), \varepsilon(\mathbf{v}))_{\mathcal{H}} \quad \forall \mathbf{u}, \mathbf{v} \in V.$$

Using (4.11), (3.19) and (3.16) it follows that

$$|A\mathbf{u} - A\mathbf{v}|_{V'} \leq |\mathcal{A}\varepsilon(\mathbf{u}) - \mathcal{A}\varepsilon(\mathbf{v})|_{\mathcal{H}} \quad \forall \mathbf{u}, \mathbf{v} \in V,$$

and keeping in mind the Krasnoselski Theorem (see for instance [11, p. 60]), we deduce that  $A : V \rightarrow V'$  is a continuous operator. Now, by (4.11), (3.19) and (3.16) we find

$$(4.12) \quad (A\mathbf{u} - A\mathbf{v}, \mathbf{u} - \mathbf{v})_{V' \times V} \geq m_{\mathcal{A}} |\mathbf{u} - \mathbf{v}|_V^2 \quad \forall \mathbf{u}, \mathbf{v} \in V,$$



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 24 of 39

Go Back

Full Screen

Close

i.e., that  $A : V \rightarrow V'$  is a monotone operator. Choosing  $\mathbf{v} = \mathbf{0}_V$  in (4.12) we obtain

$$\begin{aligned} (A\mathbf{u}, \mathbf{u})_{V' \times V} &\geq m_{\mathcal{A}} |\mathbf{u}|_V^2 - |A\mathbf{0}_V|_{V'} |\mathbf{u}|_V \\ &\geq \frac{1}{2} m_{\mathcal{A}} |\mathbf{u}|_V^2 - \frac{1}{2m_{\mathcal{A}}} |A\mathbf{0}_V|_{V'}^2 \quad \forall \mathbf{u} \in V, \end{aligned}$$

which implies that  $A$  satisfies condition (4.9) with  $\omega = \frac{m_{\mathcal{A}}}{2}$  and  $\lambda = \frac{|A\mathbf{0}_V|_{V'}^2}{2m_{\mathcal{A}}}$ . Moreover, by (4.11) and (3.19) we find

$$|A\mathbf{u}|_{V'} \leq |\mathcal{A}\varepsilon(\mathbf{u})|_{\mathcal{H}} \leq C_1^{\mathcal{A}} |\mathbf{u}|_V + C_2^{\mathcal{A}} \quad \forall \mathbf{u} \in V.$$

This inequality and (3.16) imply that  $A$  satisfies condition (4.10). Finally, we recall that by (3.28) and (3.32) we have  $\mathbf{f} - \eta \in L^2(0, T; V')$  and  $\mathbf{v}_0 \in H$ .

It follows now from Theorem 4.2 that there exists a unique function  $\mathbf{v}_\eta$  which satisfies

$$(4.13) \quad \mathbf{v}_\eta \in L^2(0, T; V) \cap C(0, T; H), \quad \dot{\mathbf{v}}_\eta \in L^2(0, T; V'),$$

$$(4.14) \quad \dot{\mathbf{v}}_\eta(t) + A\mathbf{v}_\eta(t) + \eta(t) = \mathbf{f}(t) \quad \text{a.e. } t \in (0, T),$$


$$(4.15) \quad \mathbf{v}_\eta(0) = \mathbf{v}_0.$$

Let  $\mathbf{u}_\eta : [0, T] \rightarrow V$  be the function defined by

$$(4.16) \quad \mathbf{u}_\eta(t) = \int_0^t \mathbf{v}_\eta(s) ds + \mathbf{u}_0 \quad \forall t \in [0, T].$$

It follows from (4.11) and (4.13) – (4.16) that  $\mathbf{u}_\eta$  is a unique solution of the variational problem  $PV_\eta$  and it satisfies the regularity expressed in (4.1).  $\square$





In the second step, let  $\eta \in L^2(0, T; V')$ , we use the displacement field  $\mathbf{u}_\eta$  obtained in Lemma 4.3 and we consider the following variational problem.

**Problem  $QV_\eta$ .** Find the electric potential field  $\varphi_\eta : [0, T] \rightarrow W$  such that

$$(4.17) \quad (B\nabla\varphi_\eta(t), \nabla\phi)_H - (\mathcal{E}\varepsilon(\mathbf{u}_\eta(t)), \nabla\phi)_H = (q(t), \phi)_W \quad \forall\phi \in W, t \in (0, T).$$

We have the following result.

**Lemma 4.4.**  $QV_\eta$  has a unique solution  $\varphi_\eta$  which satisfies the regularity (4.2).

*Proof.* We define a bilinear form:  $b(\cdot, \cdot) : W \times W \rightarrow \mathbb{R}$  such that

$$(4.18) \quad b(\varphi, \phi) = (B\nabla\varphi, \nabla\phi)_H \quad \forall\varphi, \phi \in W.$$

We use (4.18), (3.18) and (3.22) to show that the bilinear form  $b$  is continuous, symmetric and coercive on  $W$ , moreover using the Riesz Representation Theorem we may define an element  $q_\eta : [0, T] \rightarrow W$  such that

$$(q_\eta(t), \phi)_W = (q(t), \phi)_W + (\mathcal{E}\varepsilon(\mathbf{u}_\eta(t)), \nabla\phi)_H \quad \forall\phi \in W, t \in (0, T).$$


We apply the Lax-Milgram Theorem to deduce that there exists a unique element  $\varphi_\eta(t) \in W$  such that

$$(4.19) \quad b(\varphi_\eta(t), \phi) = (q_\eta(t), \phi)_W \quad \forall\phi \in W.$$

We conclude that  $\varphi_\eta(t)$  is a solution of  $QV_\eta$ . Let  $t_1, t_2 \in [0, T]$ , it follows from (4.17) that

$$|\varphi_\eta(t_1) - \varphi_\eta(t_2)|_W \leq C (|\mathbf{u}_\eta(t_1) - \mathbf{u}_\eta(t_2)|_V + |q(t_1) - q(t_2)|_W),$$

and the previous inequality, the regularity of  $\mathbf{u}_\eta$  and  $q$  imply that  $\varphi_\eta \in C(0, T; W)$ .  $\square$



In the third step, we let  $\theta \in L^2(0, T; L^2(\Omega))$  be given and consider the following variational problem for the damage field.

**Problem  $PV_\theta$ .** Find a damage field  $\beta_\theta : [0, T] \rightarrow H^1(\Omega)$  such that

$$(4.20) \quad \beta_\theta(t) \in K, \quad (\dot{\beta}_\theta(t), \xi - \beta_\theta(t))_{L^2(\Omega)} + a(\beta_\theta(t), \xi - \beta_\theta(t)) \\ \geq (\theta(t), \xi - \beta_\theta(t))_{L^2(\Omega)} \quad \forall \xi \in K \quad \text{a.e. } t \in (0, T),$$

$$(4.21) \quad \beta_\theta(0) = \beta_0.$$

To solve  $PV_\theta$ , we recall the following standard result for parabolic variational inequalities (see, e.g., [20, p. 47]).

**Theorem 4.5.** Let  $V \subset H \subset V'$  be a Gelfand triple. Let  $K$  be a nonempty closed, and convex set of  $V$ . Assume that  $a(\cdot, \cdot) : V \times V \rightarrow \mathbb{R}$  is a continuous and symmetric bilinear form such that for some constants  $\zeta > 0$  and  $c_0$ ,

$$a(v, v) + c_0 |v|_H^2 \geq \zeta |v|_V^2 \quad \forall v \in V.$$


Then, for every  $u_0 \in K$  and  $f \in L^2(0, T; H)$ , there exists a unique function  $u \in H^1(0, T; H) \cap L^2(0, T; V)$  such that  $u(0) = u_0$ ,  $u(t) \in K$  for all  $t \in [0, T]$ , and for almost all  $t \in (0, T)$ ,

$$(\dot{u}(t), v - u(t))_{V' \times V} + a(u(t), v - u(t)) \geq (f(t), v - u(t))_H \quad \forall v \in K.$$

We apply this theorem to problem  $PV_\theta$ .

**Lemma 4.6.** Problem  $PV_\theta$  has a unique solution  $\beta_\theta$  such that

$$(4.22) \quad \beta_\theta \in H^1(0, T; L^2(\Omega)) \cap L^2(0, T; H^1(\Omega)).$$



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 27 of 39

Go Back

Full Screen

Close

*Proof.* The inclusion mapping of  $(H^1(\Omega), |\cdot|_{H^1(\Omega)})$  into  $(L^2(\Omega), |\cdot|_{L^2(\Omega)})$  is continuous and its range is dense. We denote by  $(H^1(\Omega))'$  the dual space of  $H^1(\Omega)$  and, identifying the dual of  $L^2(\Omega)$  with itself, we can write the Gelfand triple

$$H^1(\Omega) \subset L^2(\Omega) \subset (H^1(\Omega))'.$$

We use the notation  $(\cdot, \cdot)_{(H^1(\Omega))' \times H^1(\Omega)}$  to represent the duality pairing between  $(H^1(\Omega))'$  and  $H^1(\Omega)$ . We have

$$(\beta, \xi)_{(H^1(\Omega))' \times H^1(\Omega)} = (\beta, \xi)_{L^2(\Omega)} \quad \forall \beta \in L^2(\Omega), \xi \in H^1(\Omega),$$

and we note that  $K$  is a closed convex set in  $H^1(\Omega)$ . Then, using the definition (3.35) of the bilinear form  $a$ , and the fact that  $\beta_0 \in K$  in (3.34), it is easy to see that Lemma 4.6 is a straightforward consequence of Theorem 4.5.  $\square$

In the fourth step, we use the displacement field  $\mathbf{u}_\eta$  obtained in Lemma 4.3 and we consider the following initial-value problem.


**Problem PV $_\alpha$ .** Find the adhesion field  $\alpha_\eta : [0, T] \rightarrow L^2(\Gamma_3)$  such that for a.e.  $t \in (0, T)$

$$(4.23) \quad \dot{\alpha}_\eta(t) = - (\alpha_\eta(t) [\gamma_\nu (R_\nu(u_{\eta\nu}(t)))^2 + \gamma_\tau |\mathbf{R}_\tau(\mathbf{u}_{\eta\tau}(t))|^2] - \varepsilon_a)_+,$$

$$(4.24) \quad \alpha_\eta(0) = \alpha_0.$$

We have the following result.

**Lemma 4.7.** *There exists a unique solution  $\alpha_\eta \in W^{1,\infty}(0, T; L^2(\Gamma_3)) \cap Z$  to Problem PV $_\alpha$ .*



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 28 of 39

Go Back

Full Screen

Close

*Proof.* For simplicity, we suppress the dependence of various functions on  $\Gamma_3$ , and note that the equalities and inequalities below are valid a.e. on  $\Gamma_3$ . Consider the mapping  $F_\eta : [0, T] \times L^2(\Gamma_3) \rightarrow L^2(\Gamma_3)$  defined by

$$F_\eta(t, \alpha) = -(\alpha [\gamma_\nu (R_\nu(u_{\eta\nu}(t)))^2 + \gamma_\tau |\mathbf{R}_\tau(\mathbf{u}_{\eta\tau}(t))|^2] - \varepsilon_a)_+,$$

for all  $t \in [0, T]$  and  $\alpha \in L^2(\Gamma_3)$ . It follows from the properties of the truncation operators  $R_\nu$  and  $\mathbf{R}_\tau$  that  $F_\eta$  is Lipschitz continuous with respect to the second argument. Moreover, for all  $\alpha \in L^2(\Gamma_3)$ , the mapping  $t \rightarrow F_\eta(t, \alpha)$  belongs to  $L^\infty(0, T; L^2(\Gamma_3))$ . Thus using a version of the Cauchy-Lipschitz Theorem given in Theorem 2.1, we deduce that there exists a unique function  $\alpha_\eta \in W^{1,\infty}(0, T; L^2(\Gamma_3))$  solution which satisfies (4.23)- (4.24). Also, the arguments used in Remark 1 show that  $0 \leq \alpha_\eta(t) \leq 1$  for all  $t \in [0, T]$ , a.e. on  $\Gamma_3$ . Therefore, from the definition of the set  $Z$ , we find that  $\alpha_\eta \in Z$ , which concludes the proof of the lemma.  $\square$

Finally as a consequence of these results and using the properties of the operator  $\mathcal{G}$ , the operator  $\mathcal{E}$ , the functional  $j$  and the function  $S$ , for  $t \in [0, T]$ , we consider the operator


$$\Lambda : L^2(0, T; V' \times L^2(\Omega)) \rightarrow L^2(0, T; V' \times L^2(\Omega))$$

which maps every element  $(\eta, \theta) \in L^2(0, T; V' \times L^2(\Omega))$  to the element  $\Lambda(\eta, \theta) \in L^2(0, T; V' \times L^2(\Omega))$  defined by

$$(4.25) \quad \Lambda(\eta, \theta)(t) = (\Lambda^1(\eta, \theta)(t), \Lambda^2(\eta, \theta)(t)) \in V' \times L^2(\Omega),$$

defined by the equalities

$$(4.26) \quad (\Lambda^1(\eta, \theta)(t), \mathbf{v})_{V' \times V} = (\mathcal{G}(\varepsilon(\mathbf{u}_\eta(t)), \beta_\theta(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} + (\mathcal{E}^* \nabla \varphi_\eta(t), \varepsilon(\mathbf{v}))_{\mathcal{H}} \\ + \left( \int_0^t M(t-s) \varepsilon(\mathbf{u}_\eta(s)) ds, \varepsilon(\mathbf{v}) \right)_{\mathcal{H}} + j(\alpha_\eta(t), \mathbf{u}_\eta(t), \mathbf{v}) \quad \forall \mathbf{v} \in V,$$



Title Page

Contents



Page 29 of 39

Go Back

Full Screen

Close


$$(4.27) \quad \Lambda^2(\eta, \theta)(t) = S(\varepsilon(\mathbf{u}_\eta(t)), \beta_\theta(t)).$$

Here, for every  $(\eta, \theta) \in L^2(0, T; V' \times L^2(\Omega))$ ,  $\mathbf{u}_\eta, \varphi_\eta, \beta_\theta$  and  $\alpha_\eta$  represent the displacement field, the potential electric field, the damage field and the bonding field obtained in Lemmas 4.3, 4.4, 4.6 and 4.7 respectively. We have the following result.

**Lemma 4.8.** *The operator  $\Lambda$  has a unique fixed point  $(\eta^*, \theta^*) \in L^2(0, T; V' \times L^2(\Omega))$  such that  $\Lambda(\eta^*, \theta^*) = (\eta^*, \theta^*)$ .*

*Proof.* Let  $(\eta, \theta) \in L^2(0, T; V' \times L^2(\Omega))$  and  $(\eta_1, \theta_1), (\eta_2, \theta_2) \in L^2(0, T; V' \times L^2(\Omega))$ . We use the notation  $\mathbf{u}_{\eta_i} = \mathbf{u}_i, \dot{\mathbf{u}}_{\eta_i} = \mathbf{v}_{\eta_i} = \mathbf{v}_i, \varphi_{\eta_i} = \varphi_i, \beta_{\theta_i} = \beta_i$  and  $\alpha_{\eta_i} = \alpha_i$  for  $i = 1, 2$ . Using (3.20), (3.23), (3.24), (3.25), (3.26), the definition of  $R_\nu, \mathbf{R}_\tau$  and Remark 1, we have

$$(4.28) \quad \begin{aligned} & \left| \Lambda^1(\eta_1, \theta_1)(t) - \Lambda^1(\eta_2, \theta_2)(t) \right|_{V'}^2 \\ & \leq \left| \mathcal{G}(\varepsilon(\mathbf{u}_1(t)), \beta_1(t)) - \mathcal{G}(\varepsilon(\mathbf{u}_2(t)), \beta_2(t)) \right|_{\mathcal{H}}^2 \\ & \quad + \int_0^t \left| M(t-s)\varepsilon(\mathbf{u}_1(s) - \mathbf{u}_2(s)) \right|_{\mathcal{H}}^2 ds + \left| \mathcal{E}^* \nabla \varphi_1(t) - (\mathcal{E}^* \nabla \varphi_2(t)) \right|_{\mathcal{H}}^2 \\ & \quad + C \left| p_\nu(u_{1\eta\nu}(t)) - p_\nu(u_{2\eta\nu}(t)) \right|_{L^2(\Gamma_3)}^2 \\ & \quad + C \left| \alpha_1^2(t) R_\nu(u_{1\eta\nu}(t)) - \alpha_2^2(t) R_\nu(u_{1\eta\nu}(t)) \right|_{L^2(\Gamma_3)}^2 \\ & \quad + C \left| p_\tau(\alpha_1(t)) \mathbf{R}_\tau(\mathbf{u}_{1\eta\tau}(t)) - p_\tau(\alpha_2(t)) \mathbf{R}_\tau(\mathbf{u}_{1\eta\tau}(t)) \right|_{L^2(\Gamma_3)}^2 \\ & \leq C \left( \left| \mathbf{u}_1(t) - \mathbf{u}_2(t) \right|_V^2 + \int_0^t \left| \mathbf{u}_1(s) - \mathbf{u}_2(s) \right|_V^2 ds + \left| \beta_1(t) - \beta_2(t) \right|_{L^2(\Omega)}^2 \right. \\ & \quad \left. + \left| \varphi_1(t) - \varphi_2(t) \right|_W^2 + \left| \alpha_1(t) - \alpha_2(t) \right|_{L^2(\Gamma_3)}^2 \right). \end{aligned}$$



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 30 of 39

Go Back

Full Screen

Close

Recall that  $u_{\eta\nu}$  and  $\mathbf{u}_{\eta\tau}$  denote the normal and the tangential component of the function  $\mathbf{u}_\eta$  respectively. By a similar argument, from (4.27) and (3.21) it follows that

$$(4.29) \quad \left| \Lambda^2(\eta_1, \theta_1)(t) - \Lambda^2(\eta_2, \theta_2)(t) \right|_{L^2(\Omega)}^2 \leq C \left( |\mathbf{u}_1(t) - \mathbf{u}_2(t)|_V^2 + |\beta_1(t) - \beta_2(t)|_{L^2(\Omega)}^2 \right).$$

Therefore,

$$(4.30) \quad \left| \Lambda(\eta_1, \theta_1)(t) - \Lambda(\eta_2, \theta_2)(t) \right|_{V' \times L^2(\Omega)}^2 \leq C \left( |\mathbf{u}_1(t) - \mathbf{u}_2(t)|_V^2 + \int_0^t |\mathbf{u}_1(s) - \mathbf{u}_2(s)|_V^2 ds + |\varphi_1(t) - \varphi_2(t)|_W^2 + |\beta_1(t) - \beta_2(t)|_{L^2(\Omega)}^2 + |\alpha_1(t) - \alpha_2(t)|_{L^2(\Gamma_3)}^2 \right).$$

Moreover, from (4.7) we obtain


$$(\dot{\mathbf{v}}_1 - \dot{\mathbf{v}}_2, \mathbf{v}_1 - \mathbf{v}_2)_{V' \times V} + (\mathcal{A}\varepsilon(\mathbf{v}_1) - \mathcal{A}\varepsilon(\mathbf{v}_2), \varepsilon(\mathbf{v}_1 - \mathbf{v}_2))_{\mathcal{H}} + (\eta_1 - \eta_2, \mathbf{v}_1 - \mathbf{v}_2)_{V' \times V} = 0.$$

We integrate this equality with respect to time, use the initial conditions  $\mathbf{v}_1(0) = \mathbf{v}_2(0) = \mathbf{v}_0$  and condition (3.19) to find

$$m_{\mathcal{A}} \int_0^t |\mathbf{v}_1(s) - \mathbf{v}_2(s)|_V^2 ds \leq - \int_0^t (\eta_1(s) - \eta_2(s), \mathbf{v}_1(s) - \mathbf{v}_2(s))_{V' \times V} ds,$$

for all  $t \in [0, T]$ . Then, using the inequality  $2ab \leq \frac{a^2}{m_{\mathcal{A}}} + m_{\mathcal{A}}b^2$  we obtain

$$(4.31) \quad \int_0^t |\mathbf{v}_1(s) - \mathbf{v}_2(s)|_V^2 ds \leq C \int_0^t |\eta_1(s) - \eta_2(s)|_{V'}^2 ds \quad \forall t \in [0, T].$$



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 31 of 39

Go Back

Full Screen

Close

On the other hand, from the Cauchy problem (4.23) – (4.24) we can write

$$\alpha_i(t) = \alpha_0 - \int_0^t (\alpha_i(s) [\{\gamma_\nu(R_\nu(u_{i\nu}(s)))\}^2 + \gamma_\tau |\mathbf{R}_\tau(\mathbf{u}_{i\tau}(s))|^2] - \varepsilon_a)_+ ds,$$

and then

$$\begin{aligned} & |\alpha_1(t) - \alpha_2(t)|_{L^2(\Gamma_3)} \\ & \leq C \int_0^t |\alpha_1(s) [R_\nu(u_{1\nu}(s))]^2 - \alpha_2(s) [R_\nu(u_{2\nu}(s))]^2|_{L^2(\Gamma_3)} ds \\ & \quad + C \int_0^t |\alpha_1(s) |\mathbf{R}_\tau(\mathbf{u}_{1\tau}(s))|^2 - \alpha_2(s) |\mathbf{R}_\tau(\mathbf{u}_{2\tau}(s))|^2|_{L^2(\Gamma_3)} ds. \end{aligned}$$

Using the definition of  $R_\nu$  and  $\mathbf{R}_\tau$  and writing  $\alpha_1 = \alpha_1 - \alpha_2 + \alpha_2$ , we get

$$(4.32) \quad |\alpha_1(t) - \alpha_2(t)|_{L^2(\Gamma_3)} \leq C \left( \int_0^t |\alpha_1(s) - \alpha_2(s)|_{L^2(\Gamma_3)} ds + \int_0^t |\mathbf{u}_1(s) - \mathbf{u}_2(s)|_{L^2(\Gamma_3)^d} ds \right).$$

Next, we apply Gronwall's inequality to deduce


$$|\alpha_1(t) - \alpha_2(t)|_{L^2(\Gamma_3)} \leq C \int_0^t |\mathbf{u}_1(s) - \mathbf{u}_2(s)|_{L^2(\Gamma_3)^d} ds,$$

and from the relation (3.17) we obtain

$$(4.33) \quad |\alpha_1(t) - \alpha_2(t)|_{L^2(\Gamma_3)}^2 \leq C \int_0^t |\mathbf{u}_1(s) - \mathbf{u}_2(s)|_V^2 ds.$$

We use now (4.17), (3.22), (3.23) and (3.18) to find

$$(4.34) \quad |\varphi_1(t) - \varphi_2(t)|_W^2 \leq C |\mathbf{u}_1(t) - \mathbf{u}_2(t)|_V^2.$$



Title Page

Contents



Page 32 of 39

Go Back

Full Screen

Close

From (4.20) we deduce that

$$(\dot{\beta}_1 - \dot{\beta}_2, \beta_1 - \beta_2)_{L^2(\Omega)} + a(\beta_1 - \beta_2, \beta_1 - \beta_2) \leq (\theta_1 - \theta_2, \beta_1 - \beta_2)_{L^2(\Omega)} \quad \text{a.e. } t \in (0, T).$$

Integrating the previous inequality with respect to time, using the initial conditions  $\beta_1(0) = \beta_2(0) = \beta_0$  and the inequality  $a(\beta_1 - \beta_2, \beta_1 - \beta_2) \geq 0$ , we have

$$\frac{1}{2} |\beta_1(t) - \beta_2(t)|_{L^2(\Omega)}^2 \leq \int_0^t (\theta_1(s) - \theta_2(s), \beta_1(s) - \beta_2(s))_{L^2(\Omega)} ds,$$

which implies that

$$|\beta_1(t) - \beta_2(t)|_{L^2(\Omega)}^2 \leq \int_0^t |\theta_1(s) - \theta_2(s)|_{L^2(\Omega)}^2 ds + \int_0^t |\beta_1(s) - \beta_2(s)|_{L^2(\Omega)}^2 ds.$$

This inequality combined with Gronwall's inequality leads to

$$(4.35) \quad |\beta_1(t) - \beta_2(t)|_{L^2(\Omega)}^2 \leq C \int_0^t |\theta_1(s) - \theta_2(s)|_{L^2(\Omega)}^2 ds \quad \forall t \in [0, T].$$


We substitute (4.33) and (4.34) in (4.30) to obtain

$$\begin{aligned} & |\Lambda(\eta_1, \theta_1)(t) - \Lambda(\eta_2, \theta_2)(t)|_{V' \times L^2(\Omega)}^2 \\ & \leq C \left( |\mathbf{u}_1(t) - \mathbf{u}_2(t)|_V^2 + \int_0^t |\mathbf{u}_1(s) - \mathbf{u}_2(s)|_V^2 ds + |\beta_1(t) - \beta_2(t)|_{L^2(\Omega)}^2 \right) \\ & \leq C \left( \int_0^t |\mathbf{v}_1(s) - \mathbf{v}_2(s)|_V^2 ds + |\beta_1(t) - \beta_2(t)|_{L^2(\Omega)}^2 \right). \end{aligned}$$

It follows now from the previous inequality, the estimates (4.31) and (4.35) that

$$|\Lambda(\eta_1, \theta_1)(t) - \Lambda(\eta_2, \theta_2)(t)|_{V' \times L^2(\Omega)}^2 \leq C \int_0^t |(\eta_1, \theta_1)(s) - (\eta_2, \theta_2)(s)|_{V' \times L^2(\Omega)}^2 ds.$$





Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 33 of 39

Go Back

Full Screen

Close

Reiterating this inequality  $m$  times leads to

$$|\Lambda^m(\eta_1, \theta_1) - \Lambda^m(\eta_2, \theta_2)|_{L^2(0, T; V' \times L^2(\Omega))}^2 \leq \frac{C^m T^m}{m!} |(\eta_1, \theta_1) - (\eta_2, \theta_2)|_{L^2(0, T; V' \times L^2(\Omega))}^2.$$

Thus, for  $m$  sufficiently large,  $\Lambda^m$  is a contraction on the Banach space  $L^2(0, T; V' \times L^2(\Omega))$ , and so  $\Lambda$  has a unique fixed point.  $\square$

Now, we have all the ingredients to prove Theorem 4.1.

*Proof. Existence.* Let  $(\eta^*, \theta^*) \in L^2(0, T; V' \times L^2(\Omega))$  be the fixed point of  $\Lambda$  defined by (4.25) – (4.27) and denote

$$(4.36) \quad \mathbf{u}_* = \mathbf{u}_{\eta^*}, \varphi_* = \varphi_{\eta^*}, \beta_* = \beta_{\theta^*}, \alpha_* = \alpha_{\eta^*}.$$

$$(4.37) \quad \sigma_*(t) = \mathcal{A}\varepsilon(\dot{\mathbf{u}}_*(t)) + \mathcal{G}(\varepsilon(\mathbf{u}_*(t)), \beta_*(t)) + \int_0^t M(t-s)\varepsilon(\mathbf{u}_*(s))ds + \mathcal{E}^*\nabla\varphi_*(t) \quad \forall t \in [0, T],$$


$$(4.38) \quad \mathbf{D}_*(t) = -B\nabla\varphi_*(t) + \mathcal{E}\varepsilon(\mathbf{u}_*(t)) \quad \forall t \in [0, T].$$

We prove that the quadruplet  $(\mathbf{u}_*, \varphi_*, \beta_*, \alpha_*)$  satisfies (3.40) – (3.44) and the regularities (4.1) – (4.4). Indeed, we write (4.7) for  $\eta = \eta^*$  and use (4.36) to find

$$(4.39) \quad (\ddot{\mathbf{u}}_*(t), \mathbf{v})_{V' \times V} + (\mathcal{A}\varepsilon(\dot{\mathbf{u}}_*(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} + (\eta^*(t), \mathbf{v})_{V' \times V} = (\mathbf{f}(t), \mathbf{v})_{V' \times V} \quad \forall \mathbf{v} \in V, t \in [0, T].$$

We write (4.20) for  $\theta = \theta^*$  and use (4.36) to obtain

$$(4.40) \quad \beta_*(t) \in K, \quad \left( \dot{\beta}_*(t), \xi - \beta_*(t) \right)_{L^2(\Omega)} + a(\beta_*(t), \xi - \beta_*(t)) \geq (\theta^*(t), \xi - \beta_*(t))_{L^2(\Omega)} \quad \forall \xi \in K \quad \text{a.e. } t \in (0, T).$$



Title Page

Contents

◀◀ ▶▶

◀ ▶

Page 34 of 39

Go Back

Full Screen

Close

Equalities  $\Lambda^1(\eta^*, \theta^*) = \eta^*$  and  $\Lambda^2(\eta^*, \theta^*) = \theta^*$  combined with (4.26) and (4.27) show that

$$(4.41) \quad (\eta^*(t), \mathbf{v})_{V' \times V} \\ = (\mathcal{G}(\varepsilon(\mathbf{u}_*(t)), \beta_*(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} + \left( \int_0^t M(t-s) \varepsilon(\mathbf{u}_*(s)) ds, \varepsilon(\mathbf{v}) \right)_{\mathcal{H}} \\ + (\mathcal{E}^* \nabla \varphi_*(t), \varepsilon(\mathbf{v}))_{\mathcal{H}} + j(\alpha_*(t), \mathbf{u}_*(t), \mathbf{v}) \quad \forall \mathbf{v} \in V,$$

$$(4.42) \quad \theta^*(t) = S(\varepsilon(\mathbf{u}_*(t)), \beta_*(t)).$$

We now substitute (4.41) in (4.39) to obtain


$$(4.43) \quad (\mathbf{u}_*(t), \mathbf{v})_{V' \times V} + (\mathcal{A} \varepsilon(\dot{\mathbf{u}}_*(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} \\ + (\mathcal{G}(\varepsilon(\mathbf{u}_*(t)), \beta_*(t)), \varepsilon(\mathbf{v}))_{\mathcal{H}} + \left( \int_0^t M(t-s) \varepsilon(\mathbf{u}_*(s)) ds, \varepsilon(\mathbf{v}) \right)_{\mathcal{H}} \\ + (\mathcal{E}^* \nabla \varphi_*(t), \varepsilon(\mathbf{v}))_{\mathcal{H}} + j(\alpha_*(t), \mathbf{u}_*(t), \mathbf{v}) \\ = (\mathbf{f}(t), \mathbf{v})_{V' \times V} \quad \forall \mathbf{v} \in V, t \in (0, T),$$

and (4.42) in (4.40) to get

$$(4.44) \quad \beta_*(t) \in K \text{ for all } t \in [0, T], \left( \dot{\beta}_*(t), \xi - \beta_*(t) \right)_{L^2(\Omega)} + a(\beta_*(t), \xi - \beta_*(t)) \\ \geq (S(\varepsilon(\mathbf{u}_*(t)), \beta_*(t)), \xi - \beta_*(t))_{L^2(\Omega)} \quad \forall \xi \in K.$$

Using  $\mathbf{u}_{\eta^*}$  in (4.17), by (4.36) we have:

$$(4.45) \quad (B \nabla \varphi_*(t), \nabla \phi)_H - (\mathcal{E} \varepsilon(\mathbf{u}_*(t)), \nabla \phi)_H = (q(t), \phi)_W \quad \forall \phi \in W, t \in (0, T).$$



Title Page

Contents



Page 35 of 39

Go Back

Full Screen

Close

Additionally, we use  $\mathbf{u}_{\eta^*}$  in (4.23) and (4.36) to find

$$(4.46) \quad \dot{\alpha}_*(t) = - \left( \alpha_*(t) (\gamma_\nu (R_\nu (u_{*\nu}(t)))^2 + \gamma_\tau |\mathbf{R}_\tau (\mathbf{u}_{*\tau}(t))|^2) - \varepsilon_a \right)_+ \\ \text{a.e. } t \in (0, T).$$

The relations (4.43), (4.44), (4.45) and (4.46) allow us to conclude now that  $(\mathbf{u}_*, \varphi_*, \beta_*, \alpha_*)$  satisfies (3.40) – (3.43). Next, (3.44) and the regularity (4.1) – (4.4) follow from Lemmas 4.3, 4.4, 4.6 and 4.7. Since  $\mathbf{u}_*$  and  $\varphi_*$  satisfy (4.1) and (4.2), it follows from (4.37) that

$$(4.47) \quad \sigma_* \in L^2(0, T; \mathcal{H}).$$

We choose  $\mathbf{v} = \omega \in D(\Omega)^d$  in (4.43) and by (4.37) and (3.36):

$$\rho \ddot{\mathbf{u}}_*(t) = \text{Div} \sigma_*(t) + \mathbf{f}_0(t) \quad \text{in } V' \quad \forall t \in [0, T].$$

Also, by (3.27), (3.28) and (4.47) we have:

$$\text{Div} \sigma_* \in L^2(0, T; V').$$

Let  $t_1, t_2 \in [0, T]$ . By (3.22), (3.23), (3.18) and (4.38), we deduce that

$$|\mathbf{D}_*(t_1) - \mathbf{D}_*(t_2)|_H \leq C(|\varphi_*(t_1) - \varphi_*(t_2)|_W + |\mathbf{u}_*(t_1) - \mathbf{u}_*(t_2)|_V).$$

The regularity of  $\mathbf{u}_*$  and  $\varphi_*$  given by (4.1) and (4.2) implies

$$(4.48) \quad \mathbf{D}_* \in C(0, T; H).$$

We choose  $\phi \in D(\Omega)$  in (4.45) and using (3.37) we find


$$\text{div} \mathbf{D}_*(t) = q_0(t) \quad \forall t \in [0, T].$$

By (3.29) and (4.48) we obtain

$$\mathbf{D}_* \in C(0, T; \mathcal{W}).$$

Finally we conclude that the weak solution  $(\mathbf{u}_*, \sigma_*, \varphi_*, \mathbf{D}_*, \beta_*, \alpha_*)$  of the piezoelectric contact problem  $P$  has the regularity (4.1) – (4.6), which concludes the existence part of Theorem 4.1.

*Uniqueness.* The uniqueness of the solution is a consequence of the uniqueness of the fixed point of the operator  $\Lambda$  defined by (4.25) – (4.27).  $\square$



---

Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

---

Title Page

Contents



Page 36 of 39

Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756

## References

- [1] R.C. BATRA AND J.S. YANG, Saint Venant's principle in linear piezoelectricity, *J. of Elasticity*, **38** (1995), 209–218.
- [2] H. BREZIS, Equations et inequations non linéaires dans les espaces vectoriels en dualité, *Ann. Inst. Fourier*, **18** (1968), 115–175.
- [3] O. CHAU, J.R. FERNANDEZ, M. SHILLOR AND M. SOFONEA, Variational and numerical analysis of a quasistatic viscoelastic contact problem with adhesion, *J. of Comput. and Appl. Math.*, **159** (2003), 431–465.
- [4] O. CHAU, SHILLOR AND M. SOFONEA, Dynamic frictionless contact with adhesion, *J. of Appl. Math. and Phys. (ZAMP)*, **55** (2004), 32–47.
- [5] G. DUVAUT AND J.L. LIONS, *Les Inéquations en Mécanique et en Physique*, Springer-Verlag, Berlin (1976).
- [6] M. FREMOND, Equilibre des structures qui adhèrent à leur support, *C. R. Acad. Sci. Paris*, **295**, Série II (1982), 913–916.
- [7] M. FREMOND, Adhérence des solides, *J. Mécanique Théorique et Appliquée*, **6**(3) (1987), 383–407.
- [8] M. FREMOND AND B. NEDJAR, Damage in concrete: the unilateral phenomenon, *Nuclear Engng. Design*, **156** (1995), 323–335.
- [9] M. FREMOND AND B. NEDJAR, Damage, gradient of damage and principle of virtual work, *Int. J. Solid Structures*, **33**(8) (1996), 1083–1103.
- [10] M. FREMOND, KL. KUTTLER, B. NEDJAR AND M. SHILLOR, One-dimensional models of damage, *Adv. Math. Sci. Appl.*, **8**(2) (1998), 541–570.



Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

Title Page

Contents



Page 37 of 39


Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756



- [11] O. KAVIAN, *Introduction à la théorie des points critiques et Applications aux équations elliptiques*, Springer-Verlag, (1993).
- [12] R.D. MINDLIN, Polarisation gradient in elastic dielectrics, *Int. J. Solid Structures*, **4** (1968), 637–663.
- [13] R.D. MINDLIN, Continuum and lattice theories of influence of electromechanical coupling on capacitance of thin dielectric films, *Int. J. Solids*, **4** (1969), 1197–1213.
- [14] R.D. MINDLIN, Elasticity, Piezoelectricity and Cristal lattice dynamics, *J. of Elasticity*, **4** (1972), 217–280.
- [15] J. NEČAS AND I. HLAVAČEK, *Mathematical Theory of Elastic and Elastoplastic Bodies: An Introduction*, Elsevier, Amsterdam, (1981).
- [16] M. RAOUS, L. CANGEMI AND M. COCU, A consistent model coupling adhesion, friction, and unilateral contact, *Comput. Meth. Appl. Mech. Engng.*, **177** (1999), 383–399.
- [17] J. ROJEK AND J.J. TELEGA, Contact problems with friction, adhesion and wear in orthopaedic biomechanics. I: General developments, *J. Theoretical and Applied Mechanics*, **39** (2001).
- [18] J. ROJEK, J.J. TELEGA AND S. STUPKIEWICZ, Contact problems with friction, adherence and wear in orthopaedic biomechanics. II: Numerical implementation and application to implanted knee joints, *J. Theoretical and Applied Mechanics*, **39** (2001).
- [19] M. SHILLOR, M. SOFONEA AND J.J. TELEGA, Models and Variational Analysis of quasistatic Contact, *Lect. Notes Phys.*, **655**, Springer, Berlin Heidelberg, (2004).

---

Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

---

Title Page

Contents



Page 38 of 39


Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756



- [20] M. SOFONEA, W. HAN AND M. SHILLOR, Analysis and Approximation of Contact Problems with Adhesion or Damage, *Pure and Applied Mathematics*, **276**, Chapman-Hall / CRC Press, New York, (2006).
- [21] B. TENGIZ AND G. TENGIZ, Some Dynamic of the Theory of Electroelasticity, *Memoirs on Differential Equations and Mathematical Physics*, **10** (1997), 1–53.
- [22] R.A. TOUPIN, The elastic dielectrics, *J. Rat. Mech. Analysis*, **5** (1956), 849–915.
- [23] R.A. TOUPIN, A dynamical theory of elastic dielectrics. *Int. J. Engrg. Sci.*, **1** (1963).

---

Dynamic problem with adhesion  
and damage

Selmani Mohamed

vol. 10, iss. 1, art. 6, 2009

---

Title Page

Contents



Page 39 of 39

Go Back

Full Screen

Close

journal of **inequalities**  
in pure and applied  
mathematics

issn: 1443-5756